

MC-A36

IP Camera Module — Product Specification



Specifications

General	
Model	MC-A36
Main Control Chip	SSC335
Image Sensor	SC2336P, 1/3" CMOS
Video	
Video Encoding	H.265+ / H.265 / H.264
Bitrate	0.1 – 3 Mbps (adjustable)
Frame Rate	1 – 25 fps (adjustable)
Main Stream	25FPS @ 2304×1296, 1920×1080, 1280×720
Sub Stream	D1, VGA, 640×360
Lighting	
Light Mode	Dual-light: Full-color (warm) + Infrared; Full-color only; Infrared only
IRCUT	Integrated circuit; auto / manual / timer control
Light Interface	PWM infrared + PWM warm light
Audio	
Audio Codec	G.711
Audio Interface	1-ch linear input + 1-ch linear output
Two-way Audio	Supported (voice intercom, voice broadcast, custom voice)
Smart Features	
Intelligent Analysis	Accurate human detection, custom area intrusion detection
Alarm	Dual light source alarm, sound alarm
Network	
Network Interface	1 × RJ45, 10/100M self-adaptive Ethernet
Protocols	HTTP, RTSP, DHCP, NTP, ONVIF
Mobile APP	VideoLink (iOS & Android)

SDK	Windows, Android, Linux
Power & Environment	
Power Supply	DC 12V
Current Consumption	90 mA
Working Temperature	-40°C to +65°C
Lightning Protection	GB/T17626.5, IEC61000-4-5
Dimensions	38 mm × 38 mm
Output Resolution	3MP
Image Processing	Image flip; digital wide dynamic range