

MC-L12B

IP Camera Module — Product Specification



Specifications

General	
Model	MC-L12B
Main Control Chip	SSC30KQ
Image Sensor	Sony IMX335, 5MP, 1/2.8" CMOS (blacklight starlight)
Video	
Video Encoding	H.265+ / H.265 / H.264
Bitrate	0.1 – 8 Mbps (adjustable)
Frame Rate	1 – 30 fps (adjustable)
Main Stream	30FPS @ 2592×1944, 2560×1440, 2304×1296, 1920×1080, 1280×720
Sub Stream	720×480, D1, VGA, 640×360
Lighting	
Light Mode	Dual-light: Full-color (warm) + Infrared; Full-color only; Infrared only
IRCUT	Integrated circuit; auto / external / manual / timer control
Light Interface	CDS, PWM infrared, PWM warm light
Audio	
Audio Codec	G.711
Audio Interface	1-ch linear input + 1-ch linear output
Two-way Audio	Supported
Smart Features	
Intelligent Analysis	Human detection, custom area detection
Alarm	Dual light source alarm, sound alarm
IO Interface	Motorized zoom / autofocus interface; requires compatible lens, control board and firmware
Network	
Network Interface	1 × RJ45, 10/100M self-adaptive Ethernet
Protocols	HTTP, RTSP, DHCP, NTP, ONVIF, P2P; optional GB28181, RTMP

Mobile APP	VideoLink (iOS & Android)
SDK	Windows, Android, Linux
Power & Environment	
Power Supply	DC 12V
Current Consumption	170 mA
Working Temperature	-40°C to +85°C
Lightning Protection	GB/T17626.5, IEC61000-4-5
Dimensions	38 mm × 38 mm
Other	Supports POE expansion
Image Processing	Image flip; digital wide dynamic range